



FUSES, DV/Dt, THERMAL TRIPS OPTIONAL.
 FOR B2U/H/C OMIT CTR PHASE
 FOR B6U USE MDD/xx
 FOR B6H USE MCD/xx

TOLERANCES UNLESS SPECIFIED UNLIMITED DIMENSIONS TO BE ± 0.2 ANGLES ± 0° - 30° HOLES + 0.1 - 0.02	REMOVE SHARP EDGES ALL DIMENSIONS IN MILLIMETRES CHAMFER ALL THREADS AT 45 TO ROOT DIAMETER.	POWERSEM LTD OWNS THE COPYRIGHT OF THIS DRAWING WHICH IS SUPPLIED IN CONFIDENCE AND WHICH MUST NOT BE USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SUPPLIED, AND MUST NOT BE REPRODUCED WITHOUT PERMISSION IN WRITING FROM THE OWNERS. © POWERSEM LTD.	TITLE: B6C-MCC310/xx PS292/350BF		JOB:	
			MAT'L:	SPEC.		
			FINISH:	SCALE 1:3	DRAWN PB	CHK'D MP
		ASSEMBLY ON	MDD. No		DRG.No.B 020971	
		ASSEMBLY ON	ISSUE No	1/08.02.05		

THIRD ANGLE PROJECTION