



FUSES, Dv/Dt, THERMAL TRIPS OPTIONAL.  
FOR B6H USE MCD/xx  
FOR B6U USE MDD/xx

TOLERANCES UNLESS SPECIFIED  
UNLIMITED DIMENSIONS TO BE ± 0.2  
ANGLES ± 0° 30"  
HOLES + 0.1 - 0.02

REMOVE SHARP EDGES  
ALL DIMENSIONS IN MILLIMETRES  
CHAMFER ALL THREADS AT 45 TO  
ROOT DIAMETER.

POWERSEM LTD OWNS THE COPYRIGHT OF THIS DRAWING WHICH IS  
SUPPLIED IN CONFIDENCE AND WHICH MUST NOT BE USED FOR ANY PURPOSE OTHER THAN  
THAT FOR WHICH IT IS SUPPLIED, AND MUST NOT BE REPRODUCED WITHOUT PERMISSION  
IN WRITING FROM THE OWNERS. © POWERSEM LTD.

TITLE: B6C MCC500/xx PS385/400BF

JOB:

MAT'L:

SPEC:

FINISH:

SCALE 1:3

DRAWN PB

CHK'D MP

MDD. No

ISSUE No

1/21.11.05

DRG.No.B 020985

ASSEMBLY DN:  
ASSEMBLY ON

THIRD ANGLE PROJECTION