

SINGLE PHASE FULLY CONTROLLED AC REGULATORS


GD Rectifiers

QUALITY & SERVICE

OPTIONS **FITTED LINE FUSES, INDICATORS, MICRO SWITCHES.**
Dv/Dt SUPPRESSION
MOV OVER VOLTAGE SUPPRESSION
Hi/Lo THERMAL TRIPS

WATER COOLED OPTIONS.
HIGHER VOLTAGES
IP20 ENCLOSED
STANDBY FANS

TRIGGER CIRCUITS.
CONSULT FACTORY.



ISOLATED DEVICES

DWG No	Max Output Cont Amps @ 30C	Max Output Cont Amps @ 40C	Cooling Mode	DEVICE I2T A2S *1000 @TVJ	DEVICE VRRM MAX	Height mm	Width mm	Depth mm	Weight KG
W1C 020003	40	37	NAC	1.05	1600	150	96	80	0.8
W1C 020003	55	50	NAC	9.1	1800	150	96	80	0.8
W1C 020003	65	60	NAC	20	1800	150	96	80	0.8
W1C 020005	100*/105	95	NAC	9.1	1800	180	125	180	3.2
W1C 020005	140	130	NAC	20	1800	180	125	180	3.2
W1C 020007	148	137	FAC	9.1	1800	230	125	180	4
W1C 020013N	190	170	NAC	137	1800	180	125	180	3.2
W1C 020007	200*/212	196	FAC	20	1800	230	125	180	4
W1C 020011N	220	200	NAC	137	1800	300	125	180	5.5
W1C 020015N	300	270	NAC	320	1800	300	135	180	6
W1C 020013	320	290	FAC	137	1800	230	125	180	4
W1C 020011	350	325	FAC	137	1800	350	125	180	6.5
W1C 021930	440	400	NAC	2800	1800	450	125	240	11
W1C 020015	450	419	FAC	245	1600	350	135	180	7
W1C 020015	500	465	FAC	304	1800	350	135	180	7
W1C 020015	525	487	FAC	320	1800	350	135	180	7
W1C 020021	650	620	FAC	320	1800	400	190	200	9.5
W1C 020955	770	700	FAC	1050	1800	460	125	200	10.5
W1C 020956	950	880	FAC	1050	1800	500	190	230	11.5
W1C 020957	1125	1025	FAC	2800	1800	550	190	240	14

